

**Polypropylene fabric finishing to improve properties**  
**Patent Assignee: MITR; MITSUBISHI RAYON CO LTD**

**Patent Family**

Patent Number	Kind	Date	Application Number	Kind	Date	Week	Type
JP 69029554	B					196800	B

**Priority Applications (Number Kind Date):** JP 6681914 A ( 19661214)

**Abstract:**

JP 69029554 B

Polypropylene is mixed with 1-30% of mixture of 25-5% polyethylene and 75-95% low mol. wt. n-paraffin, spun and fabric produced, and treated with treating agent after drying at > 130 deg.C but < melting pt. of polypropylene.

Can be used to improve colouring, flame-resistance, anti-static properties, crease-resistance, abrasion-resistance, anti-oxidn., softening, etc. and wash-resistant finish is obtd.

Suitable polyethylene has mol. wt. 12,000-120,000 and sp. gr. > 0.92 (obtd. by low, intermediate or high pressure process)

Suitable n-paraffin is paraffin, crystalline wax or polyethylene of average mol. wt. 500-3000.

Treating agent may be dye, pigment, size, water-proofing agent, flame-proofing agent, U. V. absorber, anti-oxidant, antistat, softener, etc.

Derwent World Patents Index

© 2005 Derwent Information Ltd. All rights reserved.

Dialog® File Number 351 Accession Number 611530